

Many more WBT parts available  
online: [www.madisound.com](http://www.madisound.com)



Many more WBT parts available  
online: [www.madisound.com](http://www.madisound.com)

Manufactured in Germany, WBT connectors are designed specifically for the high-end audio industry. The product line has expanded from that first RCA type plug to include male and female RCA type connectors, binding posts, banana plugs and spade lugs with functionally unique features that truly elevate them to the top. WBT products are very popular with audio cable and equipment manufacturers worldwide and can be found as standard equipment on many well respected brands. Please visit our web site for more complete specifications: [www.madisound.com](http://www.madisound.com)

<p><b>WBT-0610 Nextgen Banana plug</b> Fully insulated and with protective pin for European applications. Accepts up to 8 awg wire (10mm<sup>2</sup>) Red or black. Silver <b>\$72.00 each</b> Copper <b>\$36.00 each</b></p> 	<p><b>WBT-0645 Angled Banana plug</b> Fully insulated and with protective pin for European applications. Gold plated 52% copper alloy. Red, white or black. <b>\$36 each</b></p> 	<p><b>WBT-0600 Topline Banana plug</b> Produced from single piece of copper alloy. 24 carat gold plating. Up to 7awg wire (10mm<sup>2</sup>) Red, white or black. <b>\$51 each</b></p> 																																								
<p><b>WBT-0681 Nextgen Spade</b> Fully insulated spade terminal. Red, white or black. Copper: <b>\$36 each</b> Silver: <b>\$72 each</b></p> 	<p><b>WBT-0702 Topline Binding Post</b> Signature Series binding post. 24K Gold or Platinum 5 layer plated 68% copper alloy, polished R, W or B color WBT-0702.11 Gold: <b>\$95 each</b> WBT-0702.12 Platinum: <b>\$95 each</b></p> 	<p><b>WBT-0735 Topline Safety BP</b> Fully insulated 24K gold plated 68% copper alloy. Conforms to European safety standards. Red, white or black <b>\$48 each</b></p> 																																								
<p><b>WBT-0763 Midline Binding Post</b> Gold plated 52% copper alloy with 3 layer plating process. Red, white or black <b>\$30 each</b></p> 	<p><b>WBT-0765 Midline Safety BP</b> Fully insulated gold plated 52% copper alloy with 3 layer plating process. Red, white or black <b>\$34 each</b></p> 	<p><b>WBT Copper Crimp Sleeves</b></p> <table border="1"> <thead> <tr> <th>Sleeve#</th> <th>mm<sup>2</sup></th> <th>AWG</th> <th>Each</th> </tr> </thead> <tbody> <tr><td>WBT-0430</td><td>5</td><td># 20</td><td>\$1.00</td></tr> <tr><td>WBT-0431</td><td>0.75</td><td>#19</td><td>\$1.00</td></tr> <tr><td>WBT-0432</td><td>1.0</td><td>#17</td><td>\$1.00</td></tr> <tr><td>WBT-0433</td><td>1.5</td><td>#16</td><td>\$1.00</td></tr> <tr><td>WBT-0434</td><td>2.5</td><td>#14</td><td>\$1.00</td></tr> <tr><td>WBT-0435</td><td>4.0</td><td>#12</td><td>\$1.00</td></tr> <tr><td>WBT-0436</td><td>6.0</td><td>#10</td><td>\$1.00</td></tr> <tr><td>WBT-0437</td><td>10.0</td><td>#8</td><td>\$2.00</td></tr> <tr><td>WBT-0438</td><td>16.0</td><td>#6</td><td>\$2.00</td></tr> </tbody> </table>	Sleeve#	mm <sup>2</sup>	AWG	Each	WBT-0430	5	# 20	\$1.00	WBT-0431	0.75	#19	\$1.00	WBT-0432	1.0	#17	\$1.00	WBT-0433	1.5	#16	\$1.00	WBT-0434	2.5	#14	\$1.00	WBT-0435	4.0	#12	\$1.00	WBT-0436	6.0	#10	\$1.00	WBT-0437	10.0	#8	\$2.00	WBT-0438	16.0	#6	\$2.00
Sleeve#	mm <sup>2</sup>	AWG	Each																																							
WBT-0430	5	# 20	\$1.00																																							
WBT-0431	0.75	#19	\$1.00																																							
WBT-0432	1.0	#17	\$1.00																																							
WBT-0433	1.5	#16	\$1.00																																							
WBT-0434	2.5	#14	\$1.00																																							
WBT-0435	4.0	#12	\$1.00																																							
WBT-0436	6.0	#10	\$1.00																																							
WBT-0437	10.0	#8	\$2.00																																							
WBT-0438	16.0	#6	\$2.00																																							
<p><b>WBT-0780 Brass Binding Post</b> Velours Chromium finished solid brass binding post. Red, white or black. <b>\$28 each</b></p> 	<p><b>WBT Silver Solder - Tin Based</b> 4% fine silver content. Halogen-free flux protects against etching of surfaces. Low melting temp 180°C/356°F. RoHS WBT-0805 0.9mm, 42g, 10m <b>\$37</b> WBT-0825 0.8mm, 250g, 73m <b>\$113</b> WBT-0845 1.2mm, 500g, 57m <b>\$220</b> <b>WBT Silver Solder - Lead Based</b> 4% fine silver content. Halogen-free flux protects against etching of surfaces. Melting temp 219°C/426°F. Not RohS. WBT-0800 0.9mm, 42g, 10m <b>\$24</b> WBT-0820 0.8mm, 250g, 73m <b>\$81</b> WBT-0840 1.2mm, 500g, 57m <b>\$147</b></p> 	<p><b>WBT Copper Crimp Sleeves with Insulated Collar</b></p> <table border="1"> <thead> <tr> <th>Sleeve#</th> <th>mm<sup>2</sup></th> <th>AWG</th> <th>Each</th> </tr> </thead> <tbody> <tr><td>WBT-0441</td><td>1.5</td><td>#16</td><td>\$2.00</td></tr> <tr><td>WBT-0442</td><td>2.5</td><td>#14</td><td>\$2.00</td></tr> <tr><td>WBT-0443</td><td>4.0</td><td>#12</td><td>\$2.00</td></tr> <tr><td>WBT-0444</td><td>6.0</td><td>#10</td><td>\$3.00</td></tr> <tr><td>WBT-0445</td><td>10.0</td><td>#8</td><td>\$3.00</td></tr> <tr><td>WBT-0446</td><td>16.0</td><td>#6</td><td>\$4.00</td></tr> </tbody> </table>	Sleeve#	mm <sup>2</sup>	AWG	Each	WBT-0441	1.5	#16	\$2.00	WBT-0442	2.5	#14	\$2.00	WBT-0443	4.0	#12	\$2.00	WBT-0444	6.0	#10	\$3.00	WBT-0445	10.0	#8	\$3.00	WBT-0446	16.0	#6	\$4.00												
Sleeve#	mm <sup>2</sup>	AWG	Each																																							
WBT-0441	1.5	#16	\$2.00																																							
WBT-0442	2.5	#14	\$2.00																																							
WBT-0443	4.0	#12	\$2.00																																							
WBT-0444	6.0	#10	\$3.00																																							
WBT-0445	10.0	#8	\$3.00																																							
WBT-0446	16.0	#6	\$4.00																																							
<p><b>WBT-SPACER \$3.00</b>  <b>WBT-T6 Screw \$2.00</b>  <b>WBT-0488 Torx Key \$6</b> </p>	<p><b>Aluminum Mounting Plates</b> Available in Clear and Black anodized WBT-0530 Single <b>\$85 each</b> WBT-0531 Bi-wire <b>\$115 each</b> WBT-0532 Bi-wire <b>\$125 each</b></p>																																									