

# DESCANT *IN-WALL & IN-CEILING SPEAKERS*

Madisound is pleased to offer Descant architectural sound systems for wall and ceiling installation. We think this is an excellent approach to hi-fi sound, without the requirement of significant space for loudspeaker placement. Descant speakers are a good choice for Audio, Video or Commercial applications.

The spin out clamps allow easy installation. Using the template provided, simply cut a hole in the drywall or paneling. Attach the speaker wire to the input terminals and clamp the wall material between the grill frame and the clamps. **New Construction kits** are available for all but the square flange coaxial for **\$19.00 a pair**.

## **RCX-619 6.5" Coaxial 2-Way \$155 / pair**

## **RCX-825 & SCX-825 8" Coaxial 2-Way \$170 / pair**

The RCX-825 (round) and SCX-825 (square) coaxial speakers are constructed with an 8" polypropylene cone woofer with rubber surround and a pivotal 1" textile dome tweeter. The crossovers are designed with 12dB parts on the woofer and 6dB parts on the tweeter, resulting in 12dB mirrored slopes.

The RCX-619 (round) has a polypropylene cone with a rubber surround and pivotal ¾" textile dome tweeter. The crossover is 12dB/12dB.

The concentric design of a coaxial speaker makes this systems suitable for mounting in the ceiling. With the tweeter mounted in the center of the woofer, no matter where you are standing in relationship to the speaker, you will be equal distance from both the woofer and tweeter. This system performs equally as well when mounted in the wall.



### Specifications RCX-825 & SCX-825:

Impedance:	8 ohm	Sensitivity:	88dB
Frequency:	45 to 20kHz	Color:	white
Power:	75 Watts	X-over freq.:	3.5kHz
Dimensions R800:	10 ¾" diameter x 3 ½" deep		
Dimensions SQ800:	10 1/16" square x 3 ½" deep		

### Specifications RCX-619:

Impedance:	8 ohm	Sensitivity:	89dB
Frequency:	65 to 20kHz	Color:	white
Power:	50 Watts		
X-over freq.:	3.5kHz		
Dimension:	9" diameter x 2 7/8" deep		

## **RCX-619CH \$89.00 Each**

This is a chambered version of the RCX-619. The fire rated plastic chamber will allow this speaker to be used in many installations requiring a fire resistant chamber.



## **RCX-825CH \$97.00 Each**

This is a chambered version of the RCX-825. The fire rated plastic chamber will allow this speaker to be used in many installations requiring a fire resistant chamber.

